

Anyone looking for a reliable and undemanding workhorse is well served with the POS-310 Eco GT II. With this model, 4POS has developed an ergonomic all-in-one POS solution which runs absolutely quiet. It operates completely without fans and is thus easy to maintain. With its ultra-sleek and very stylish design, this energyefficient POS terminal requires a minimum amount of space. Equipped with a 15" resistive touchscreen, it is very user-friendly and optimally designed for use in hospitality.



Touch System POS-310 Eco GT II



1. Ultra-Slim Housing with Advanced Fanless Thermal Design



2. Optional Customer Display 15"



3. Optional MSR and iButton



4. Optional VFD Customer Display







POS-310 Eco GT II

Display Size Brightness	Plastic Plastic D36 Intel Celeron J1900 2.0GHz (fanless) Intel HD Graphics Intel HD Graphics 1 x DDR3L-1600 S0-DIMM up to 8GB IS" TFT LCD with LED backlight 250 cd/m2 1024 x 768
CPU Chipset / GPU System Memory Display / Touch Display Size Brightness	D36 Intel Celeron J1900 2.0GHz (fanless) Intel HD Graphics 1 x DDR3L-1600 S0-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
CPU Chipset / GPU System Memory Display / Touch Display Size Brightness	Intel Celeron J1900 2.0GHz (fanless) Intel HD Graphics 1 x DDR3L-1600 SO-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
Chipset / GPU System Memory Display / Touch Display Size Brightness	Intel Celeron J1900 2.0GHz (fanless) Intel HD Graphics 1 x DDR3L-1600 SO-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
Chipset / GPU System Memory Display / Touch Display Size Brightness	Intel HD Graphics 1 x DDR3L-1600 S0-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
System Memory Display / Touch Display Size Brightness	Intel HD Graphics 1 x DDR3L-1600 S0-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
System Memory Display / Touch Display Size Brightness	1 x DDR3L-1600 SO-DIMM up to 8GB 15" TFT LCD with LED backlight 250 cd/m2
Display / Touch Display Size Brightness	15" TFT LCD with LED backlight 250 cd/m2
Display Size Brightness	250 cd/m2
Brightness	250 cd/m2
-	
Maximum Resolution	1021/11/00
Touch Sreen Type	Resistive
Tilt Angle (Degree)	0° ~ 90°
Storage	
Primary Device Bay	1 x 2.5 SATA (HDD or SSD)
External I/O	עפט ווי שנוא צ.ט אווי (ערט וי שנוי)
USB	5 x USB (4 x USB 2.0 + 1 x USB 3.0)
Parallel Port	1 x D-Sub 25F
Serial/COM	3 x COM ports with RJ-45 (5V/12 power selectable by BIOS)
LAN	1 x RJ-45 (10/100/1000 Mbit)
VGA out	1 x D-Sub (15 pin) with Power over VGA (activated via BIOS)
Cash Drawer	1 x RJ-11 with 12V or 19V
Speaker	1 x 2W
Audio	N/A
Control / Power	
Power Button	1
Power Supply	External 65W/19V
Environment	
EMC & Safety	FCC Class A, CE, LVD
Operating Temperature	5° C ~ 35° C
Operation Humidity	20% ~ 85% RH non condensing
Options	
Second Display	15" Customer Display without Touch / VFD Display (2x20, 5mm character)
WLAN	802.11 a/b/g USB Wireless LAN
Magnetic Card Reader	3 track MSR (via USB)
iButton	1 (via USB)
Finger Print Reader	1 (via USB)
Dimension	
Dimensions (W x L x H)	364 x 210 x 370 mm
Weight	
	5.57 kg
Colour	
	Black
OS Support	
	Windows embedded 7 standard; Windows Embedded Compact 7; Windows 7; POSReady 7; Windows embedded 8; Windows 8.1; Linux

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

