



Stylish Design
Bezefree Touch
Various Sizes

Decide on the MxM-315 EyeTOUCH and your troubles with cable clutter are over! Well-conceived in every detail, Swiss design meets advanced technology. Cables are tucked away in the base stand and thus rendered invisible at the POS. Suited for direct on-counter placement, wall mounting, kiosk installation, with VESA mounts – unlimited in use (VGA, DVI, USB ports, integrated USB hub with five outputs) and very flexible, it can be placed anywhere.



Touch Monitor

MxM-308 EyeTOUCH
MxM-310 EyeTOUCH
MxM-315 EyeTOUCH



1. Unique base design with smart cable management



2. Optional 8" & 10.4" customer display



3. Viewing angle up to 90°



4. Rich I/O board



5. 8" & 10.4" stand alone models



6. Optional alternative base stands EyeSTAND POS and FlexSTAND or VESA mount



MxM-308 EyeTOUCH

MxM-310 EyeTOUCH

MxM-315 EyeTOUCH



Model Name	MxM-308 EyeTOUCH	MxM-310 EyeTOUCH	MxM-315 EyeTOUCH
Housing			
Housing	Plastic	Plastic	Die-cast Magnesium-Aluminium
Bezel	Plastic	Plastic	Plastic
Stand	Aluminium	Aluminium	Aluminium
Mount	VESA 75		
Display / Touch			
Display Size	8"	10.4"	15"
Touch Technology	Resistive or Capacitive (AG coating)	Resistive or Capacitive (AG coating)	Resistive or Capacitive (AG coating)
Brightness	250 cd/m2	250 cd/m2	350cd/m2
Maximal Resolution	800 x 600	800 x 600	1024 x 768
Contrast Ratio	800:1	500:1	800:1
Response Time	25 ms	20 ms	8 ms
Viewing Angle	140 degrees (H) / 130 degrees (V)	140 degrees (H) / 110 degrees (V)	160 degrees (H) / 160 degrees (V)
Input Video Signal	VGA / USB B Type	VGA / USB B Type	VGA or DVI
External I/O Ports			
VGA	1	1	1
DVI	N/A	N/A	1
USB	1 x	1 x	2 x bottom / 1 x right / 2 x left / 1 x Type B
Audio	N/A	N/A	Line-in (optional)
Serial/Com	N/A	N/A	1
Control / Power			
Power Button	1	1	1
Power Supply	External, DC 12V (mini DIN) / USB none	External, DC 12V (mini DIN) / USB none	External, DC 12V
Environment			
Power consumption	6W (VGA/miniDIN), 2.5W (USB)	6W (VGA/miniDIN), 2.5W (USB)	30W
EMC & Safety	FCC, CE		
Operating Temperature	0 ~ 40° C		
Operating Humidity	20% ~ 80%		
IP	N/A	N/A	IP65 sealed front panel with touch screen
Options			
Display	N/A	High Brightness Panel	N/A
Magnetic Card Reader	N/A	N/A	3 tracks MSR (via USB)
2nd Display	N/A	N/A	8" or 10.4" LCD (bezelfree)
Alternative Stand	EyeSTAND CDx	EyeSTAND CDx	EyeSTAND POS High / Low / FlexSTAND
Dimension			
(W x D x H)	202 x 142 x 190 mm	244 x 197 x 211 mm	361 x 200 x 339 mm
Weight			
	1.2 kg	1.35 kg	4.76 kg
Colour			
	Black or Glossy White		
OS Support			
	Windows XP, 7, 8.x, 10 / Linux		

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

V1804