

Decide on the MCM-310 EyeTOUCH II and your troubles with cable clutter are over! Well-conceived in every detail, Swiss design meets advanced technology. Cables are tucked away in the base stand and thus rendered invisible at the POS. Suited for direct on-counter placement, wall mounting, kiosk installation, with VESA mounts unlimited in use (VGA, DP, USB) and very flexible, it can be placed anywhere.



Touch Monitor MCM-310 Eyetouch II



1. Unique base design with smart cable management



2. High luminance display
- Up to 600 nits with viewing angle up to 170°



- Rich Video options

 Powered VGA
 Display Port
 - Video over USB



4. 2D Scanner



MCM-310 EyeTOUCH II



Model Name	MCM-310 EyeTOUCH II	
Housing		
Housing	Die-Cast Aluminium	
Bezel	Plastic	
Stand	Aluminium	
Mount	VESA 75	
Display / Touch		
Display Size	10.4"	
Touch Technology	Capacitive (AG coating) / non Touch (option)	
Format	4:3	
Brightness	250 cd/m2	600 cd/m2
Maximal Resolution	800 x 600	1024 x 768
Contrast Ratio	500:1	900:1
Response Time	20 ms	30 ms
Viewing Angle	140 degrees (H) / 110 degrees (V)	170 degrees (H) / 170 degrees (V)
Input Video Signal	VGA / DP / USB-B (Display Link)	
External I/O Ports		
VGA	1 x	
DP	1 x	
USB	1 x	
Audio	N/A	
Serial/Com	N/A	
Control / Power		
Power Button	1	
Power Supply	Power over VGA none / VGA and DP external, DC 12V / USB none	
Environment		
Power consumption	4.8W (800 x 600) / 9W (1024 x 768) / Standby <0.5W	
EMC & Safety	FCC, CE	
Operating Temperature	0 ~ 40° C	
Operating Humidity	20% ~ 80%	
IP	N/A	
Options		
Scanner	1 x 2D Scanner	
Magnetic Card Reader	N/A	
2nd Display	N/A	
Alternative Stand	EyeSTAND CDx	
Dimension		
(W x D x H)	245.5 x 135 x 214.4 mm	
Weight		
	1.10 kg without stand / 1.65 with stand	
Colour		
	Black / Shiny White	
OS Support		
	Windows 8.x, 1	0 / Linux

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

