

# ESSENCE OUTDOOR

## Application


Self-order & Payment, Information, Check-in

## Market

Quick Service Restaurants, Petrol Stations, EV Charging Stations

## Purpose

The ESSENCE OUTDOOR is specifically designed to enable self-service applications in the outdoor domain under the supervision of an employee. The ESSENCE OUTDOOR is therefore the high-quality outdoor kiosk for your business.



# ESSENCE OUTDOOR

## Product specs

Type	Specification
Power Supply	230 VAC - 50/60Hz internally
Power Consumption - Typical*	113W
Power Consumption - Maximum*	150W
Material	RVS304, Powder Coated
Dimensions - without roof	500 x 329 x 2095 mm
Dimensions - with roof (WxDxH)	580 x 581 x 2342 mm
Weight*	185 kg

*\*Indicative weight only. Exact figure depending on configuration and accessories*

## Installation requirements:

Placement	Fully outdoor (no additional canopy needed)
Orientation	Display must not point South
Geographical Location	Corrosion Class: Max. C4
	Product may not be installed in ATEX zones
Foundation	To be prepared by customer. (see Installation Site Requirement document)
Mounting	Bolted to foundation. (see Installation Site Requirement document)
Power / network supply	From ground (see Installation Site Requirement document)
Required power cable/connector	230V Cable - Without plug Cable length - above ground = 2 meter
Required network cable/connector	Data cable - With RJ45 connector Cable length - above ground = 2 meter
Required protected end group	16A

## Environmental conditions:

Ingress Protection	IPX4
Impact Protection	IK07
Operating Temperature	-15°C up to 40°C
Storage Temperature	10°C up to 30°C
Humidity	5% up to 95% non-condensing

## Hardware specs:

Type	Standard/Optional	Specification
Screen	Standard	Size 32 inch
		Resolution 1920 x 1080
		Brightness 1500 nits
		Viewing angle 178° / 178°
PC	Optional	Pan Oston PC - Celeron 4GB - 64GB
		Windows 10 Enterprise Pan Oston PC - i3 8GB - 250GB
		Pan Oston PC - i5 8GB - 250GB
		Others on request
Power Supply	Standard	Integrated PanPower PSU
Printer	Optional	Custom VKP-80III
Scanner	Optional	Newland FM3080
Pin & Chip	Optional	Feig cVEND PIN, Cardreader
		Verifone UX100, UX300, UX400
		Others on request
Climate Control	Standard	Active heating and cooling
Network	Optional	Teltonika 4G Router + Antenna
Network Entry	Optional	Optical fiber

## Product Options:

Colour scheme	Optional	Single colour
		Two-tone
Colour coating	Standard	Light colours: All RAL colours
		Dark colours - Infrared reflectant: RAL 9005 - Black (Fine textured)
	Optional	Dark colours - Infrared reflectant: RAL3005, 5004, 7016, 9007 (Gloss) RAL6005, 8017, 7021 (Semi-gloss) RAL5013, 9005 (Matt) RAL5011, 6009, 7026 (Fine textured)
	MOQ = 12pcs	
LED Light bar along side wall	Optional	Single colour. Warm white
Roof + Additional lighting	Optional	The roof will provide additional lighting. The roof will not provide the user protection from the elements.

### Pan Oston B.V.

**Adress** Hertzstraat 1  
8102 PK Raalte  
The Netherlands

**P.O. Box** P.O. Box 222  
8100 AE Raalte  
The Netherlands

**Phone** +31 572 35 77 55  
**Email** info@panoston.nl  
**Website** panoston.nl