

Pure in the structure, purely in the design, purely in the application.
The POS-213 PurePOS is a POS system that provides the latest technology with a clear design and high functionality. User-oriented features allow for a scope that meets the needs.

The nearly frameless panel construction and the fantastic 2256 x 1504 DPI resolution enable a visual language that renders your interface and graphics razor-sharp.

Request our new POS-213 PurePOS.

All-in-One POS-213 PurePOS





1. 13.5" touch screen with thin bezel of only 7mm



2. Elegant and sleek design shared with customer display sister model MCM-213 PureTOUCH



3. Core I/O ports behind hinge cover



4. Cable management



5. Modern, state of the art interfaces



6. Optional UCB-213
PureHUB / PureHUB Plus
Connectivity Box for extended
connectivity







| Model Name | POS-213 PurePOS |
|-------------------------------|--------------------------------------------------------------------------------------------------------|
| Housing | |
| Material | Plastic (Panel PC), Die-cast Magnesium-Aluminium (Covers) |
| Mount | VESA 75 + VESA Mount metal sheet 75 to 100 |
| Mainboard | |
| CPU | Intel Apollo Lake N4200 Quad-Core |
| GPU | Intel HD Graphics |
| NVRAM | 256KB |
| System Memory | 4GB up to 8GB |
| Cooling | Passive (fanless) |
| Display / Touch | |
| Display Size | 13.5" TFT LCD with LED backlight |
| Brightness | 320 cd/m2 |
| Maximum Resolution | 2256 x 1504 |
| Format | 3:2 |
| Touch Screen Type | Projected Capacitive, Anti Glare Coated Glass |
| Storage | |
| Primary Device Bay | M.2 2280 SSD 128GB (default) up to 512GB |
| Main Unit External I/O Ports | |
| USB | 2 x USB 2.0 (on I/O panel), 2 x USB 3.0 (on I/O panel), 1 x USB 2.0 (optional behind right side cover) |
| LAN | 1 x RJ-45 (10/100/1000 Mbit) |
| Second Display | 1 x USB Type-C (with screwlock) / 1 x Mini DisplayPort (with screwlock) |
| DC in | 1 x 24V 4Pin |
| DC out | 1 x 24V 3Pin |
| Link to Connectivity Box | 1 x USB Type-C (with screwlock) |
| Speaker | 1 x 1W |
| Control/Indicator | |
| Power Button | LED Button (red light Off, green light On, green light flashing S3 Mode) |
| Power Supply | 120W/24V (Panel PC only) / 180W/24V (with UCB-213 PureHUB / PureHUB Plus) |
| Environment | |
| EMC & Safety | CE & FCC |
| Operating Temperature | 0~40° C |
| IP . | IP65 sealed front panel with touch screen |
| Options | |
| Wireless Communication | 802.11a/c (under left side of cover), Bluetooth 4.2, NFC, RFID 13.56MHz (Mifare or LEGIC) |
| Connectivity | UCB-213 PureHUB / PureHUB Plus |
| Expansion | Module bay under right side cover (USB 2.0) |
| Pen | Active stylus pen |
| Dimension (W x H x D), Weight | |
| Panel PC only | 307 x 224 x 38mm, 1.8kg |
| Colour | |
| | Black with a silver frame |
| OS Support | |
| | Windows 10, Linux |
| | |

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

